

Convertitori DC/DC / Convertidores DC/DC



OUTPUT VOLTAGE (Vdc)	12					24			
AVAILABLE POWER (W)	50	75	100	150	180	100	200	300	300
OUTPUT CURRENT (A constant)	4,16	6,25	8,3	12,5	15,5	4,2	8,3	12,5	13
DIMENSIONS	A	A	A	B	C	A	B	B	C
PARALLEL CONNECTION	Y	Y	Y	Y	N	Y	Y	Y	N
INPUT VOLTAGE RANGE (Vdc)	30-150	30-150	30-150	30-130	15-110	30-150	30-130	30-130	28-110
PROTECTION DEGREE	IP65								

Model	A	B	C
Weight (kg)	0,5	1,2	0,5
Dimensions L x D x H (mm)	110 x 100 x 35	115 x 130 x 55	90 x 91 x 37
Technical specifications	see technical drawings		

Amplio range di tensioni d'ingresso / Tensioni di uscita 12V, 24V (tensioni speciali a richiesta).

Modelli IP65

Possibilità di connessione in parallelo (in base al modello).

Amplia gama multi voltaje en entrada / Voltaje salida 12V, 24V (V especiales por encargo)

Modelos IP65

Conexión en paralelo disponible (depende del modelo)